

# Commercial Energy Storage System

# SmartESS 60kW/100kWh

Compact energy storage solution designed for small C&I loads integrating modular hybrid inverters, high efficiency lithium batteries with intelligent BMS, HVAC, fire suppression system and cloud monitoring.



## Integrated

- Modular Hybrid PCS
- 6.65kWh (1C) Safest LiFePO4 Battery modules
- Intelligent BMS
- Remote monitoring
- IP54 outdoor cabinet with fire suppression and HVAC system

## Flexible

- Wide Battery DC Voltage Range
- Modular design easy expansion up to 10 units in parallel
- Optimized for both on-grid and off-grid (island mode) applications
- Easy installation and maintenance
- Various applications such as peak shaving, frequency regulation, EV Charging, Solar + Storage, Micro-Grid, self Consumption Optimization

## Reliable

- Antiseismic and more than 25 years design life
- Maximum safety utilizing Tier 1 lithium battery cells
- Long lifespan with over 10000 cycles and 15 years design life

## Technical Specifications

### SmartESS100 Parameters

System Cabinet	
Rated Output Power	63 kW
Battery Capacity of the ESS	99.84 kWh
Battery Configuration	15S1P
Dimensions (WxHxD)	1035 x 2050 x 1280 mm
Weight Including Battery Modules	<1500 Kg
Operating Range / Storage Temperature	-30°C to +55°C / -40°C to +60°C
Operating Humidity Range	0 - 100 %
Maximum Operating Altitude	4000m
IP Degree	IP54, Outdoor
Communication Ports and Protocols	CAN , Ethernet / CAN, Modbus TCP, IP
Cooling Method	Industrial Air Conditioning
DC Lighting Protection	Type II
Battery Pack	
Cell Material	LFP
Nominal Capacity	6.65 kWh
Nominal Voltage	51.2 V
Rated Capacity	130A
Maximum Charging/Discharging Current	≤ 1.0 C
Power Conversion System	
Rated Output Voltage	230/400 V
Maximum PV Input	50 kWp
Maximum Current	101A
Rated Grid Frequency	50/60 Hz
Maximum Efficiency	99.00%
Protections	AC Overcurrent Protection, AC Overvoltage Protection, AC Surge Protection, AC Short Circuit Protection, Antiisland Protection, DC Reverse Connection Protection, Straight Surge Protection
Compliances	EN 62477, EN IEC 61000
Grid Support	L/HVRT, Active and Reactive Power Control
Certified	CE/CQC

## Highlights



HIGH FLEXIBILITY



EASY INSTALLATION



SMART MONITORING



STRONG LOAD ADAPTABILITY